

Applications

- Ultra Shallow Water
- Cable / Pipeline / Umbilical Trenching
- Cable / Pipeline / Umbilical Deburial
- Freespan rectification
- Jack-up Spudcan Clearing & Cleaning
- UXO & Salvage Deburial
- Rock Dump & Drill Cutting Removal
- Subsea Structure Deburial and Access

Capabilities

Max Jet Flow	350 L/s
Max Jet Pressure	350 kPa
Max Jet Power	122 kW
Minimum Operating Depth	1 m


Benefits

- Jet trenching solution for cohesive and noncohesive soils
- Asset safe, non-contact operation
- Highly qualified & experienced operators
- Real time sonar monitoring of service
- 24 hour Engineering support
- Tailored Hybrid Jet Trenching Solutions
- Designed, manufactured and maintained in-house by Rotech Engineering

Personnel

- 6 Rotech operators for 24hr operations

Example RS3 Equipment Spread



Key

No.	Item	Dimensions (m)	Weight (kg)
1	RS3 Tool	2.23 x 2.05 x 1.71	3,500*
2	Single Tool HPU	4.06 x 2.44 x 2.90	7,500
3	Hydraulic Umbilical Winch	2.26 x 2.56 x 2.42	10,000
4	Spares Container (Rotech)	6.10 x 2.45 x 2.9	12,000
5	Umbilical Chute	2.90 x 0.84 x 1.17	1,000
6	Hydraulic Deck Tugger (optional)	1.00 x 1.16 x 0.68	576
7	Tugger HPU (optional)	1.50 x 0.80 x 1.62	1,000
8	Universal Roller Fairlead (optional)	1.55 x 0.56 x 1.14	500
9	Control Cabin (optional)	3.05 x 2.45 x 2.60	5,000

* All weights are approximate and may vary depending on exact configuration

For over three decades Rotech have pioneered the development of cutting edge subsea Controlled Flow Excavation (CFE) technology. A dedication to innovation has seen Rotech continually evolve and enhance our specialised equipment to meet demand and deliver for the needs of many major clients in the subsea oil & gas and energy sectors.